


Datasheet

1.25 Gbps Single Fiber Bidirectional 20 km SFP Transceivers

SFP-GD-BX34 and SFP-GD-BX43



Highlights

- SFP transceiver
- Data Rates: 1.25 Gbps
- Protocols:
 - Gigabit Ethernet
- Single-mode fiber
- Single fiber, bidirectional
- Two wavelength options:
 - Tx 1310 nm and Rx 1490 nm
 - Tx 1490 nm and Rx 1310 nm
- 0 to 20 km
- Simplex LC or SC connector
- Digital Diagnostics (SFF-8472)
- Hot-swap
- Industrial temperature models available

Overview

Small Form-Factor Pluggable (SFP) interfaces from MRV Communications provide flexible high speed links in a small industry standard package. They deliver the deployment options and inventory control that network administrators demand for growing networks.

SFPs are designed to Multi-Source Agreement (MSA) standards to ensure network equipment compatibility. They are a perfect addition to MRV's extensive lines of networking equipment.

Visit the MRV website at www.mrv.com or contact your nearest authorized MRV Communications dealer for more information.

Specifications Overview

Data Rate	1.25 Gbps
Tx Wavelength for SFP-GD-BX34	1310 nm
Tx Wavelength for SFP-GD-BX43	1490 nm
Tx Power (Minimum)	-7 dBm
Tx Disable	Yes
Rx Wavelength for SFP-GD-BX34	1480 to 1500 nm
Rx Wavelength for SFP-GD-BX43	1260 to 1360 nm
Rx Sensitivity	-20 dBm
Rx Saturation	-3 dBm
Damage Threshold	0 dBm
Operating Temperature Range	-5 to 70 °C
Operating Temperature Range (TH Models)	-40 to 85 °C
Power Consumption	1 Watt

Datasheet

Transmitter Specifications (Optical)

Parameter	Symbol	Min	Max	Unit	Notes
Optical Power	P_{op}	-7	0	dBm	-
Optical Crosstalk	XT	-	-40	dB	-
Average Launch Power Tx_Off	P_{off}	-	-45	dBm	-
Extinction Ratio	ER	6	-	dB	-
Eye Mask	-	Compliant with IEEE 802.3			-
Optical Rise/Fall Time (20%~80% values)	t_r / t_f	-	260	ps	-
Mean Wavelength for SFP-GD-BX34	λ	1260	1360	nm	-
Mean Wavelength for SFP-GD-BX43	λ	1480	1500	nm	-
Spectral Width (RMS) for SFP-GD-BX34	$\Delta\lambda$	-	3.5	nm	-
Spectral Width (RMS) for SFP-GD-BX43	$\Delta\lambda$	-	0.88	nm	-
Relative Intensity Noise	RIN	-	-120	dB/Hz	-
Transmitter Reflectance	-	-	-12	dB	-
Reflection Tolerance	r_p	-	12	dB	-

Receiver Specifications (Optical)

Parameter	Symbol	Min	Max	Unit	Notes
Receiver Power Low	$R_{sens, low}$	-	-20	dBm	1
Receiver Power High	$R_{sens, high}$	-3	-	dBm	1
Damage Threshold For Receiver	$P_{in, damage}$	0	-	dBm	-
Wavelength for SFP-GD-BX34	λ	1480	1500	nm	2
Wavelength for SFP-GD-BX43	λ	1260	1360	nm	-
Receiver Reflectance	RX_r	-	-12	dB	-
LOS Assert	-	-45	-	dBm	-
LOS De-assert	-	-	-20	dBm	-
LOS Hysteresis	-	0.5	-	dB	-

- Notes:**
1. Measured at 10^{-12} BER, PRBS 2⁷-1, 6 dB ER
 2. Receiver performance can be maintained over a broader wavelength range of 1480 nm to 1580 nm

Digital Diagnostics

Parameter	Range	Accuracy	Unit	Calibration	Formula
Temperature	-5 to 70	± 3	$^{\circ}C$	External	$T_c(C) = T_{slope} * T_{ad}(16 \text{ bit signed twos complement value}) + T_{offset}$
Temperature (TH Models)	-40 to 85	± 3	$^{\circ}C$	External	$T_c(C) = T_{slope} * T_{ad}(16 \text{ bit signed twos complement value}) + T_{offset}$
Voltage	0 to V_{CC}	0.1	V	External	$V(\text{Volts}) = V_{slope} * V_{ad}(16 \text{ bit unsigned integer}) + V_{offset}$
Bias Current	0 to 120	5	mA	External	$I(\text{mA}) = I_{slope} * I_{ad}(16 \text{ bit unsigned integer}) + I_{offset}$
TX Power	-7 to 0	± 3 dB	dBm	External	$Tx_PWR(\mu W) = Tx_PWR_{slope} * Tx_PWR_{ad}(16 \text{ bit unsigned integer}) + Tx_PWR_{offset}$
RX Power	-20 to -3	± 3 dB	dBm	External	$RX_PWR(\mu W) = A_0 + A_1 * x + A_2 * x^2 + A_3 * x^3 + A_4 * x^4$

Datasheet

General Operations

Parameter	Symbol	Min.	Max.	Unit	Notes
Supply Voltage	V_{cc}	3.135	3.465	V	-
Total Current	I_{cc}	-	300	mA	-
Power Supply Noise Rejection	PSR	100	-	mV _{p-p}	-
Operating Case Temperature	T_{opr}	-5	70	°C	1
Operating Case Temperature (TH Models)	T_{opr}	-40	85	°C	1
Storage Temperature	T_{stg}	-40	85	°C	-
Data Rate	DR	-	1.25	Gbps	-

Notes: 1. Please refer to ordering information

Transmitter Specifications (Electrical)

Parameter	Symbol	Min	Max	Unit	Notes
Input Differential Impedance	R_{in}	80	120	Ω	-
PECL Differential Data Input Swing	$V_{in, p-p}$	250	1200	mV	-
TxFault_Fault	V_{fault}	2	V _{cc}	V	-
TxFault_Normal	V_{normal}	V _{ee}	V _{ee} + 0.5	V	-
TxDisable_Disable	V_d	2	V _{cc}	V	-
TxDisable_Enable	V_{en}	V _{ee}	V _{ee} + 0.8	V	-

Receiver Specifications (Electrical)



Parameter	Symbol	Min	Max	Unit	Notes
PECL Differential Data Output Swing	$V_{out, p-p}$	185	800	mV	-
Data Output Rise/Fall Time	t_r / t_f	-	260	ps	-

Electrical Specifications and Timing

Parameter	Symbol	Min	Max	Unit	Notes
Tx Disable Negate Time	t_{on}	-	1	ms	-
Tx Disable Assert Time	t_{off}	-	10	μ s	-
Time to Initialize, Including Reset of Tx Fault	t_{init}	-	300	ms	-
TX Fault Assert Time	t_{fault}	-	100	μ s	-
Tx Disable to Reset	t_{reset}	10	-	μ s	-
LOS Assert Time	$t_{loss_{on}}$	-	100	μ s	-
LOS De-Assert Time	$t_{loss_{off}}$	-	100	μ s	-
Serial ID Clock Rate	f_{serial_clock}	-	100	kHz	-
RX_LOS Voltage (High)	RX_LOS_H	2	-	V	-
RX_LOS Voltage (Low)	RX_LOS_L	-	0.8	V	-
LOS Output Voltage-Fault	$V_{LOS_{fault}}$	2	V _{cc}	V	-
LOS Output Voltage-Normal	$V_{LOS_{normal}}$	V _{ee}	V _{ee} + 0.5	V	-
MOD_DEF (0:2)-High	V_H	2	V _{cc}	V	-
MOD_DEF (0:2)-Low	V_L	V _{ee}	V _{ee} + 0.5	V	-

Datasheet

Pin	Function	Name / Description	Notes
1	V _{eeT}	Module Transmitter Ground	-
2	TX_FAULT	Open Collector	-
3	TX_DISABLE	Internally Pulled High	-
4	MOD_DEF2	Serial Data Input	-
5	MOD_DEF1	Serial Clock Input	-
6	MOD_DEF0	Internally Grounded	-
7	NC	Not Connected	-
8	LOS	Open Collector	-
9	V _{eeR}	Module Receiver Ground	-
10	V _{eeR}	Module Receiver Ground	-
11	V _{eeR}	Module Receiver Ground	-
12	RXD-	Receiver Data Negative	-
13	RXD+	Receiver Data Positive	-
14	V _{eeR}	Module Receiver Ground	-
15	V _{ccR}	Module Receiver Power Supply	-
16	V _{ccT}	Module Transmitter Power Supply	-
17	V _{eeT}	Module Transmitter Ground	-
18	TXD+	Transmitter Data Positive	-
19	TXD-	Transmitter Data Negative	-
20	V _{eeT}	Module Transmitter Ground	-

Outline Drawing (LC connector)

Outline Drawing (SC connector)




Datasheet

Ordering Information

Model	Description	Data Rate (Gbps)	Wavelength (nm)		Connector Type	Digital Diagnostics	Bail Latch Color	Distance Range (km)
			Tx	Rx				
SFP-GD-BX34	1.25 Gbps SFP Single Fiber Bidirectional Transceiver	1.25	1310	1490	LC	Yes	Blue	0 -20
SFP-GD-BX43	1.25 Gbps SFP Single Fiber Bidirectional Transceiver	1.25	1490	1310	LC	Yes	Purple	0 -20
SFP-GD-BX34TH	1.25 Gbps SFP Single Fiber Bidirectional Transceiver <i>(Temperature Hardened)</i>	1.25	1310	1490	LC	Yes	Blue	0 -20
SFP-GD-BX43TH	1.25 Gbps SFP Single Fiber Bidirectional Transceiver <i>(Temperature Hardened)</i>	1.25	1490	1310	LC	Yes	Purple	0 -20
SFP-GD-BX34SC	1.25 Gbps SFP Single Fiber Bidirectional Transceiver	1.25	1310	1490	SC	Yes	Blue	0 -20
SFP-GD-BX43SC	1.25 Gbps SFP Single Fiber Bidirectional Transceiver	1.25	1490	1310	SC	Yes	Purple	0 -20

Regulatory and Industry Compliances

Class 1 Laser Product, complies with EN 60825-1 and 21 CFR 1040.10 except for deviations pursuant to Laser Notice No. 50. dated June 24, 2007
MSA SFF-8074i; Telcordia GR-468, Digital Diagnostic SFF-8472;
Certified by one or more of the following agencies: TÜV, UL, CSA
RoHS Directive; China RoHS; California RoHS Law, REACH Directive SVHC; WEEE Directive
The Quality Management System is certified to ISO 9001 by QMI-SAI Global
The Environmental Management System is in compliance with ISO 14001

Warnings

Handling Precautions: This device is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.

Laser Safety: Radiation emitted by laser devices can be dangerous to human eyes. Avoid eye exposure to direct or indirect radiation.

MRV has more than 50 offices throughout the world. Addresses, phone numbers and fax numbers are listed at www.mrv.com. Please e-mail us at info@mrv.com or call us for assistance.

MRV Los Angeles
20415 Nordhoff Street
Chatsworth, CA 91311
800-338-5316
818-773-0900

MRV Boston
300 Apollo Drive
Chelmsford, MA 01824
800-338-5316
978-674-6800

MRV International
Business Park Moerfelden
Waldeckerstrasse 13
64546 Moerfelden-Walldorf
Germany
Tel. (49) 6105/2070
Fax (49) 6105/207-100

All statements, technical information, and recommendations related to the products herein are based upon information believed to be reliable or accurate. However, the accuracy or completeness thereof is not guaranteed, and no responsibility is assumed for any inaccuracies. Please contact MRV Communications for more information. MRV Communications and the MRV Communications logo are trademarks of MRV Communications, Inc. Other trademarks are the property of their respective holders.